OHL DR Series

MODEL OHL-DR

FEATURES

- Range of Performance Louvers
- Range of Blade Profiles
- Single or Double Doors
- Obstructed Line of Sight
- Standard or Selected Hardware

CONSTRUCTION

Holyoake Louvered Door Systems are constructed entirely of 6063 T5 extruded aluminium, mechanically locked together ensuring a solid resilient structure. All louvers are manufactured to the highest fabrication and performance standards.

OPTIONS

- Powder Coat finishes (Duratec warranty coatings available on request)
- Natural Anodised finish
- Aluminium or Stainless Steel bird mesh
- Aluminium Blanking

 The Holyoake Louver Door System has been designed to incorporate all of the features that you could think of in an architectural door and still be compatible with our entire range of outside louvers.

All on site fixings are designed to be concealed using the supplied cover bend once the door has been installed. The doors are hung with high quality stainless steel hinges that have been selected to take the load of a large door.

HOLYOAKE LOUVERED DOOR FEATURES


- The outer frame of the door system can be supplied in either flanged or channel form. If the frame is supplied in channel form, a sealant cavity is left to allow for a flush mounted installation.
- The inside edge of the door frame has an edge to trim to. This edge also gives the option of fitting timber reveals. If the door is installed in a thinner wall this edge has been designed to be easily removed.
- The louver doors are constructed with a rigid square frame to fix the hinges and the lock set to. The doors come standard with a high quality lock set.
- The front of the door has a seal on the closing face to eliminate door rattle. This also gives the door a positive closure feeling.
- The hinged posts of the doors have a security lip on the inside edge. This lip is there to prevent the doors being lifted out even if the hinge pins are removed.

With all of these features incorporated into the Holyoake Louver Door System as standard it now makes the appearance and installation of our louver doors second to none.






DIMENSIONAL DATA



REAL PROPERTY

FRAME HEIGHT (OPENING -10mm)

Front Elevation



COMBINED FIRE HYDRANT & SPRINKLER BOOSTER