

Deflection Grilles Building Product Information Sheet

Version 1.0 - Issued 11/06/24

Product

Product name Single/Double Deflection Grilles

Product type Grilles

Product Identifiers DDL/DDS/SDL/SDS

Product description and intended use

- The DD and SD are sidewall deflection grilles with either two sets or one set of deflection blades respectively.
- The DD and SD have high free area and therefore can handle high air flow capacities while giving good throws.
- Both variations are custom made to order from aluminium.
- These grilles are available with a 25mm flange which is compatible with the removable core system.
- Optional opposed blade dampers are available and are custom made to fit over the neck of each diffuser.
- The L code suffix specifies front bladers along the long size whereas the S suffix denotes the front blades along the short side.

Relevant NZBC clauses

- Clause B2 Durability: Performance B2.3.1 (c) 5 Years
- Clause H1 Energy Efficiency: Performance H1.3.6

Contributions to compliance with NZBC

- **B2:** The lifespan of the DD/SDs will vary based on the environment it is installed in. For a standard HVAC installation, the DD/SDs would provide a durability of a minimum of 5 years. Excessively corrosive or harmful environments or exposure to fire, heat or water will reduce the lifespan of the DD/SDs.
- **H1:** When installed in a commercial building as a supply diffuser the DD/SDs must be designed to have a maximum pressure drop of 40Pa.
- **H1:** When installed in a commercial building as an exhaust grille the DD/SDs must be designed to have a maximum pressure drop of 30Pa.

Relevant standards

N/A

Conditions and limitations of use

- The DD/SDs should be specified by a suitably qualified engineer.
- The DD/SDs should be installed by a suitably qualified and trained tradesperson.

Warnings and bans

The DD/SDs is **not** subject to a warning or ban under section 26 of the Building Act 2004.



Installation details and product datasheet

The DD/SDs product datasheets and installation details can be found on our website.

Maintenance requirements

N/A

Manufacture details

Manufacture location New Zealand

Manufactured by Price Holyoake (NZ) Ltd T/A Holyoake Air

Management Solutions by Price

Manufacturer NZBN9429048831215Manufacturer websiteHolyoakebyprice.nz

Auckland address for service 67 Greenmount Drive,

East Tamaki, Auckland 2013

Auckland office email Auckland@holyoake.com

Auckland office phone number (09) 274 4144

Wellington address for service 89 Main Road,

Tawa,

Wellington 5028

Wellington office email Wellington@holyoake.com

Wellington office phone number (04) 232 2722

Christchurch address for service 27 Waller Terrace,

Addington,

Christchurch 8011

Christchurch office email Christchurch@holyoake.com

Christchurch office phone number (03) 366 6545

Declaration

Price Holyoake (NZ) Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Version History

Version	Created	Date	Changes from previous document
number	by	issued	
V1.0	ST	11/06/24	First issue